

SUBMITTAL SHEET

150F

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE

.025" Aluminum

COLOR/FINISH

Luxacote Lighthouse White – #0401

Luxacote Natural – #7080

Other _____

**PERFORATION
PATTERN**

Non-Perforated

#124 – Vent Panels (Max 10% of ceiling)

TRIM

Wall Angle

Other _____

EXPOSURE

Interior

Exterior - Design Wind Pressure (required) _____ PSF

Shop Drawings required on all Exterior projects.

To Contact Us:

5015 Oakbrook Parkway, Suite 100

Norcross, GA 30093

phone: 800.366.4327


fax: 770.806.0214

HDarchitectural.com

HunterDouglas 
Architectural

PERFORATIONS – VENT PANELS

#124



Perforation diam: .078 in.
Open area: 15%

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50

Weight: 0.75 lbs./sq.ft.

Wind load: Per code

Designed and tested in accordance with the requirements of the Florida Building Code 5th edition (2014), including the High Velocity Hurricane Zone (HVHZ) provisions and Miami-Dade requirements.

Miami-Dade County, Florida NOA No. 14-1222.04 (expires March 19, 2020)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

– Cotton White: LR = 0.81