

# SUBMITTAL SHEET

## 300C

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**Return Form To Hunter Douglas**

**E-mail: [ceiling.samples@hunterdouglas.com](mailto:ceiling.samples@hunterdouglas.com)**

**Fax: 770.806.0214**

**SUBSTRATE** .028" Aluminum

**COLOR/FINISH**  Cotton White – #0280  
 Natural – #7163  
 Other # \_\_\_\_\_

**PERFORATION PATTERN**  Non-Perforated  #160/#124 \_\_\_\_\_ % Vent Panels (Max 10% of ceiling)

\* Exterior perforations available as vent panels only.

**ACOUSTICAL BACKER**  Black Non-Woven  
 Black Polywrapped Pad  
 None  
\* For use with interior perforated material only.

**ACOUSTICAL RATING**  \_\_\_\_\_ (NRC)

**TRIM**  Wall Angle  Floating J-Trim  Other \_\_\_\_\_

**EXPOSURE**  Interior  
 Exterior - Design Wind Pressure (required) \_\_\_\_\_ PSF

**Shop Drawings required on all Exterior projects.**


**To Contact Us:**  
5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
HDarchitectural.com

**HunterDouglas**   
Architectural

## PERFORATIONS


Perforated panels improve acoustical performance as well as create aesthetic effects.

**#124**



Perforation diam: .078 in.  
Open area: 15%

**#160**



Perforation diam: .060 in.  
Open area: 23%

## SOUND ABSORPTION (NRC) SUMMARY\*

Sound absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Perforation Pattern	% Open Area	Acoustical Infill	NRC
#160	23%	Non-Woven Acoustic .....	0.70
		1" - 1 pcf Polywrapped Fiberglass & Non-Woven Acoustic .....	0.95

\* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

## PHYSICAL DATA

**Substrate:** Aluminum

**Warranty:** 1 year

**Seismic rating:** Zones A,B,C,D,E,F

**Fire rating:** Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

**Weight:** Varies 0.5 – 0.75 lbs./sq.ft.

**Wind load:** Per code (for exterior applications)

Designed and tested in accordance with the requirements of the Florida Building Code 5th edition (2014), including the High Velocity Hurricane Zone (HVHZ) provisions and Miami-Dade requirements.

**Miami-Dade County, Florida NOA No. 16-0125.06 (expires May 5, 2021)**

**Recycled content:** Up to 92%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81