
EXTERIOR - LINEAR PLANK 300C



Project: Luxury Auto Mall, Tucson, AZ; 300C Exterior

KEY FEATURES

- Panel width: 12" nom. [300 mm]
- Panel lengths: 3' to 19'-8"
- Bevel-edge design
- Waste reduction with factory fabricated dimensional material
- Downweight: reduce dead load with lightweight aluminum
- Interior and exterior applications
- Compatible with industry standard lighting, HVAC, speaker, fire safety, and security services
- Perforated panels available for ventilation
- Factory assembled access doors available

COLORS & FINISHES

Standard colors Natural and Cotton White shown. Client-specific colors available. Minimum quantities may apply. Colors are for illustrative purposes. See page 178 for all colors and finishes.

Standard colors



Natural

Maple








Woodwright[™] finishes use our painted wood-look finish. See page 180 for all finishes.








Cherry





PERFORATION PATTERNS

Standard patterns shown. Scale shown: 1:1, unless otherwise noted.





Non-perforated

Pattern #124 (Ventilation Panels)

PHYSICAL DATA

Substrate: Aluminum Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 0.5 – 0.75 lbs./sq.ft.

Wind load: Per code

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81

Acoustical ratings – NRC: See page 190

REVIT files available for BIM contributions, see website for details.

LEED V4 CREDITS

EA: Optimize Energy Performance MR: Building Product Disclosure **EQ:** Low-Emitting Materials **EQ:** Indoor Air Quality Assessment

EQ: Daylight

CERTIFICATIONS

GREENGUARD Gold Certified HPDs & EPDs – available upon request