

SUBMITTAL SHEET

BOX SERIES

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE Aluminum

PROFILE Box 2 Box 4 Box 6 Box 8 (.032" thickness only)

COLOR/FINISH Cotton White – #0280 Other _____
 Natural – #7163

FILLER STRIP Box Flat Recessed Closure – Matte Black – #1883 Open Reveal
 Box Flat Recessed Closure – Cotton White – #0280
* Filler Strip required for all Exterior applications.

PERFORATION PATTERN Box 2 Non-Perforated Box 6 Non-Perforated #160
Box 4 Non-Perforated #160 Box 8 Non-Perforated #160

ACOUSTICAL BACKER Black Non-Woven
 Black Polywrapped Pad
 None

ACOUSTICAL RATING (NRC) _____

TRIM Wall Angle Edgeline (interior only) _____
 Floating J-Trim End Caps

EXPOSURE Interior
 Exterior – Design Wind Pressure (required) _____ PSF

Shop Drawings required on all Exterior projects.

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
HDarchitectural.com


HunterDouglas 
Architectural

SUBMITTAL SHEET **BOX SERIES**

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#160



Perforation diam: .060 in.
Open area: 23%
Box 4, 6, 8 only

SOUND ABSORPTION (NRC) SUMMARY*

Product	Acoustical Infill	NRC
Box 2, non-perforated, open reveal	1.5" – 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, non-perforated, open reveal	1.5" -1.5 pcf Polywrapped Fiberglass	0.75
Box 4, Perforated #160 (23% Open Area), open reveal	1.5"-1.5 pcf Polywrapped Fiberglass	0.90
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure strip	1.5" -1.5 pcf Polywrapped Fiberglass	0.85
Box 6, non-perforated, open reveal	1.5" -1.5 pcf Polywrapped Fiberglass	0.65
Box 6, Perforated #160 (23% Open Area), open reveal	1.5"-1.5 pcf Polywrapped Fiberglass	0.90
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5"-1.5 pcf Polywrapped Fiberglass	0.80
Box 8, non-perforated, open reveal	1.5" -1.5 pcf Polywrapped Fiberglass	0.50
Box 8, Perforated #160 (23% Open Area), open reveal	1.5"-1.5 pcf Polywrapped Fiberglass	0.90
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5"-1.5 pcf Polywrapped Fiberglass	0.85

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

Weight: Varies 0.5 – 0.75 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81