SUBMITTAL SHEET DEEP BOX SERIES

Specification Se Ceiling Type		
Return Form To Hunter Douglas E-mail: ceiling.samples@hunterdouglas.com Fax: 770.806.0214		

SUBSTRATE	Aluminum		
PROFILE	☐ Deep Box 2 ☐ Deep Box 4 ☐ Deep Box 6 ☐ Deep Box 8 (.032" thickness only)		
COLOR/FINISH	☐ Cotton White — #0280 ☐ Natural — #7163 ☐ Other #		
FILLER STRIP	☐ Box Flat Recessed Closure — Matte Black — #1883 ☐ Open Reveal ☐ Box Flat Recessed Closure — Cotton White — #0280 * Filler Strip required for all Exterior applications.		
ACOUSTICAL RATING	☐ (NRC) (Achieved via Open Reveals)		
TRIM	☐ Wall Angle ☐ Edgeline (interior only) ☐ Floating J-Trim ☐ End Caps		
EXPOSURE	☐ Interior ☐ Exterior - Design Wind Pressure (required)PSF		

Shop Drawings required on all Exterior projects.



SUBMITTAL SHEET **DEEP BOX SERIES**

SOUND ABSORPTION (NRC) SUMMARY*

Product	Acoustical Infill	NRC
Deep Box 2, non-perforated, open reveal	1" — 1.5 pcf Polywrapped Fiberglass	0.65
Deep Box 2, non-perforated, open reveal	2" — 1.5 pcf Polywrapped Fiberglass	0.90

^{*} Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting.

PHYSICAL DATA

Substrate: Aluminum **Warranty**: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: \leq 25, Smoke \leq 50

– Film on metal: Flame spread: \leq 25, Smoke \leq 50

– Wood veneer on metal: Flame spread: \leq 25, Smoke \leq 55 (for interior applications)

Weight: Varies 0.5 - 0.75 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81