SUBMITTAL SHEET

HIGH PROFILE SERIES™ VERTICALLY CURVED

Specification Section Ceiling Type Deturn Forms To Human Boundary					
Return Form To Hunter Douglas E-mail: ceiling.samples@hunterdouglas.com Fax: 770.806.0214					

SUBSTRATE	Extruded Aluminum				
PROFILE	■ Beam (1 1/2" x * Length — minimum	6 3/8") m 4'-0", maximum 20'-0"			
BEAM SPACING	□ 6"	□ 8"	□ 12"	☐ Other	
VERTICAL CURVATURE	Radius:(Minimum 48") * For multiple radii, or two radii on the same beam, contact Hunter Douglas.				
COLOR/FINISH	Beam Finish ☐ Cotton White - ☐ Natural — #716 ☐ Other #	33			
	Hanger Bracket Finish ☐ Black ☐ White ☐ Painted to match plenum				
END CAPS	☐ Yes	□ No			
EXPOSURE	✓ Interior Only				

Shop Drawings required on all High Profile projects.



HDarchitectural.com

SUBMITTAL SHEET HIGH PROFILE SERIES™ VERTICALLY CURVED

PHYSICAL DATA

Substrate: Aluminum Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 2.0 - 4.0 lbs./sq.ft.

Wind load: N/A

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81