

# SUBMITTAL SHEET

## MULTI-BOX SERIES

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**Return Form To Hunter Douglas**

**E-mail: [ceiling.samples@hunterdouglas.com](mailto:ceiling.samples@hunterdouglas.com)**

**Fax: 770.806.0214**

**SUBSTRATE:  
ALUMINUM**

- |                                |                                     |                           |
|--------------------------------|-------------------------------------|---------------------------|
| <input type="checkbox"/> Box 2 | <input type="checkbox"/> Deep Box 2 | } (Select all that apply) |
| <input type="checkbox"/> Box 4 | <input type="checkbox"/> Deep Box 4 |                           |
| <input type="checkbox"/> Box 6 | <input type="checkbox"/> Deep Box 6 |                           |
| <input type="checkbox"/> Box 8 | <input type="checkbox"/> Deep Box 8 |                           |

**COLOR/FINISH**

- Cotton White – #0280  
 Natural – #7163  
 Other \_\_\_\_\_

**FILLER STRIP**

- Box Flat Recessed Closure – Matte Black – #1883  
 Box Flat Recessed Closure – Cotton White – #0280  
\* Filler Strip required for all Exterior applications

**PERFORATION  
PATTERN**

- |       |   |                               |   |   |
|-------|---|-------------------------------|---|---|
| Box 2 | <input type="checkbox"/> Non-Perforated | Deep Box 2                    | <input type="checkbox"/> Non-Perforated |   |
| Box 4 | <input type="checkbox"/> Non-Perforated | <input type="checkbox"/> #160 | Deep Box 4                              | <input type="checkbox"/> Non-Perforated |
| Box 6 | <input type="checkbox"/> Non-Perforated | <input type="checkbox"/> #160 | Deep Box 6                              | <input type="checkbox"/> Non-Perforated |
| Box 8 | <input type="checkbox"/> Non-Perforated | <input type="checkbox"/> #160 | Deep Box 8                              | <input type="checkbox"/> Non-Perforated |

**ACOUSTICAL  
BACKER**

- Black Non-Woven  
 Black Polywrapped Pad  
 Black PVC Pad  
 None

**ACOUSTICAL RATING**

- (NRC) \_\_\_\_\_

**TRIM**

- Wall Angle  Edgeline (interior only) \_\_\_\_\_  
 J-Trim  End Caps

**EXPOSURE**

- Interior  
 Exterior - Design Wind Pressure (required) \_\_\_\_\_ PSF

Shop Drawings required on all Exterior projects.

**To Contact Us:**

5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
[www.hunterdouglasarchitectural.com](http://www.hunterdouglasarchitectural.com)


**HunterDouglas**   
Architectural

# SUBMITTAL SHEET MULTI-BOX SERIES

## PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#160



Perforation diam: .060 in.  
Open area: 23%  
**(Box 4, 6 and 8 only)**

## SOUND ABSORPTION (NRC) SUMMARY\*

Product	Acoustical Infill	NRC
Box 2, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.75
Box 4, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85
Box 6, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.65
Box 6, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.80
Box 8, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.50
Box 8, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85

\* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

## TESTING RESULTS

**Surface Burning** ..... Class A (ASTM E84)  
Flame  $\leq$  25  
Smoke  $\leq$  50

**Light Reflectance** ..... LR1  
(White)

**Stability under humidity** ..... Yes

**IAQ Friendly** ..... Yes – Mold & Mildew Resistant

**VOCs** ..... No

**Fiber Content** ..... No

**Moisture Resistance** ..... Excellent

**Life Cycle** ..... Excellent

## SUSTAINABILITY

Hunter Douglas aluminum ceilings are manufactured from material with a minimum of 70% recycled content

- 40% is post-consumer
- 30% is pre-consumer

