

SUBMITTAL SHEET

TAVOLA™ FRAMES

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE: .025" .032" Other _____

ALUMINUM

BEAM SIZES
(Width x Height)

<input type="checkbox"/> 1" x 2"	<input type="checkbox"/> 1-1/2" x 2"	<input type="checkbox"/> 2" x 2"	<input type="checkbox"/> 3" x 2"	<input type="checkbox"/> 4" x 2"	<input type="checkbox"/> 6" x 2"
<input type="checkbox"/> 1" x 3"	<input type="checkbox"/> 1-1/2" x 3"	<input type="checkbox"/> 2" x 3"	<input type="checkbox"/> 3" x 3"	<input type="checkbox"/> 4" x 3"	<input type="checkbox"/> 6" x 3"
<input type="checkbox"/> 1" x 4"	<input type="checkbox"/> 1-1/2" x 4"	<input type="checkbox"/> 2" x 4"	<input type="checkbox"/> 3" x 4"	<input type="checkbox"/> 4" x 4"	<input type="checkbox"/> 6" x 4"
<input type="checkbox"/> 1" x 5"	<input type="checkbox"/> 1-1/2" x 5"	<input type="checkbox"/> 2" x 6"	<input type="checkbox"/> 3" x 6"	<input type="checkbox"/> 4" x 6"	<input type="checkbox"/> 6" x 6"
<input type="checkbox"/> 1" x 6"	<input type="checkbox"/> 1-1/2" x 6"				<input type="checkbox"/> Other _____

MODULE SIZES 24" x 24" 24" x 48" 48" x 48" Other _____

COLOR/FINISH

Cotton White-#0280
 Black-#1883
 Natural-#7163
 Other _____

INFILL PANEL **Types Needed:**

Lights Diffusers Sprinklers Security Speakers Other _____

Contact Hunter Douglas to specify details per each infill panel type.

TRIM

Wall Angle
 J Trim
 Floating: Beam Punched 1-Side
 Other _____

EXPOSURE Interior Only

Shop Drawings required on all Tavola™ Frames projects.

To Contact Us:
 5015 Oakbrook Parkway, Suite 100
 Norcross, GA 30093
 phone: 800.366.4327
 fax: 770.806.0214
 HDarchitectural.com

HunterDouglas 
 Architectural

SUBMITTAL SHEET **TAVOLA™ FRAMES**

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 0.5 – 2.0 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 85%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

– Cotton White: LR = 0.81