

SUBMITTAL SHEET

V-BAFFLE FINS

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE	<input checked="" type="checkbox"/> .025" Aluminum		
PANEL SIZE	<input type="checkbox"/> V100 (4")	<input type="checkbox"/> V150 (6")	<input type="checkbox"/> V200 (8") (If multiple, select all that apply)
CARRIER SYSTEM	<input type="checkbox"/> Standard - Fixed	<input type="checkbox"/> Movable	<input type="checkbox"/> Pivot Clip (T-Grid)
PANEL SPACING	<input type="checkbox"/> 4"	<input type="checkbox"/> 6"	<input type="checkbox"/> 8"
PANEL BULB	<input type="checkbox"/> 1" Dia. Panel Bulb	<input type="checkbox"/> None	
COLOR/FINISH	Panel <input type="checkbox"/> Cotton White – #0280 <input type="checkbox"/> Natural – #7163 <input type="checkbox"/> Other # _____	Bulb <input type="checkbox"/> Cotton White – #0280 <input type="checkbox"/> Natural – #7163 <input type="checkbox"/> Other # _____	
EXPOSURE	<input checked="" type="checkbox"/> Interior Only		

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
HDarchitectural.com

HunterDouglas 
Architectural

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50

Weight: Varies 0.5 – 1.0 lbs./sq.ft.

Wind load: N/A

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

– Cotton White: LR = 0.81