SUBMITTAL SHEET

WALL SYSTEM

Return Form To Hunter Douglas E-mail: ceiling.samples@hunterdoug	
Ceiling Type	
Specification Section	
Project Name	

SUBSTRATE: ALUMINUM	□ .050"	□ .063"			
SIZES (6" x 12" up to 48" x 120" or 120" x 48")	☐ 6" x 12" ☐ 12" x 24" ☐ 12" x 48" ☐ 12" x 60" ☐ 12" x 72"	☐ 12" x 96" ☐ 24" x 24" ☐ 24" x 48" ☐ 24" x 60" ☐ 24" x 72"	☐ 24" x 96" ☐ 30" x 30" ☐ 30" x 60" ☐ 42" x 42" ☐ 42" x 48"	☐ 48" x 48" ☐ 48" x 120" ☐ 120" x 48" ☐ Other	
COLOR/FINISH	☐ Cotton White — #0280 ☐ Other #		□ Natural – #7163		
PERFORATION PATTERN	□ 103 □ 106	☐ 119 ☐ Non-Perforated			
PERF BORDER	☐ 1/4" Standard	☐ Other			
ACOUSTICAL BACKER	☐ Black Polywrapped ☐ None ☐ Other	Pad			
ACOUSTICAL	(NRC)				
TRIM		☐ Outside Corner ☐ Base Trim ☐ Doorframe Trim			
	☐ Color/Finish: #	☐ Color/Finish: #			
BASE	4 "	□ 6"			
	☐ Color/Finish: #				
EXP0SURE	✓ Interior Only				

To Contact Us:5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214


HDarchitectural.com





SUBMITTAL SHEET WALL SYSTEM

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.







Perforation dia: .118 in.

PHYSICAL DATA

Substrate: Aluminum Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

– Film on metal: Flame spread: \leq 25, Smoke \leq 50

Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

Weight: Varies Wind load: N/A

Recycled content: Up to 85%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81