

### Monaco®6 1 Inch Blind Model # MONG

Competitively positioned 1 inch horizontal aluminum window covering for commercial applications.



#### Key Features

Valance free design

Headrail: .94 inch high X 1.35 inch wide

6 gauge thick slats

21.5mm ladder spacing

Limited lifetime warranty

LightMaster™ option available

Integrated headrail

Box brackets standard

Integrated brackets available

#### Product Overview

The Monaco 6® 1 Inch Blind, considered the tenant standard, represents Levolor's competitively positioned horizontal blind backed by a lifetime limited warranty. Committed to both durability and aesthetics, the Monaco 6 1 Inch blind provides the high quality of economical choice.

The durable and slim headrail, made of roll-formed painted steel, offers the choice of an integrated headrail or an add on valance.

The 6 gauge thick slats are made of 5000 series magnesium aluminum alloy. This material provides overall strength and resiliency, assuring a quality look for the life of the blind. The Monaco 6 Inch blind's 21.5mm ladder spacing ensures tight closure and optimum light control.


## Product Specifications

For more detailed specifications please reference Monaco®6 1 Inch Blind Product Guide Specifications.


### Products

- A. Monaco®6 1 Inch Blind manufactured by LEVOLOR (model #MON6)
- B. Lifetime Limited Warranty
- C. Materials:


- Headrail** shall be of .02 inch thick painted steel, .94 inch high x 1.35 inch wide. All hardware shall be enclosed in the metal headrail.
- Tilter** mechanism shall be a sealed housing with lubricated worm and gear mechanism to prevent wear.
- Tilt Wand** shall be transparent with a round fluted cross section approximately  $\frac{3}{10}$  inch in diameter with 6 grooves for non-slip grip.
- Cord Lock** shall have steel shields with brass rollers and shall be crashproof.
- Drums and Cradles** shall be provided for each ladder. Drums and cradles shall be of engineering polymer.
- Installation Brackets/Box Brackets** shall be a one piece .035 inch thick painted steel with a hinged safety locking front cover to permit removal of headrail without lateral movement.
- Ladders** (slat supports): Distance between slats shall not exceed 21.5mm.
- Slats** shall be of 5000 series magnesium aluminum alloy.  
Slats shall be nominally 1 inch wide and the thickness of the slat shall be 6 gauge.
- Bottomrail** shall be of .023 inch thick painted steel.
- Options** shall include:
  - a. Cord Cleat
  - b. End Mount Adapter
  - c. Extension Brackets
  - d. Hidden Brackets
  - e. Hold-Down Brackets
  - f. Integrated Bracket
  - g. LightMaster™  
(model # MARK1P)
  - h. 2 Slat Framed Vogue® Valance



Box Bracket Detail



Integrated Bracket Detail



Box Bracket



Hold-down Bracket

**HunterDouglas**   
Architectural

800.727.8953 | HDarchitectural.com