

SUBMITTAL SHEET

PLAZA™

Project Name _____

Specification Section _____

Ceiling Type _____

**SUBSTRATE: COMPOSITE
ALUMINUM HONEYCOMB**

1" (nom.) Panel Height

SIZES

(Max. 48" x 120")

- | | | |
|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> 24" x 48" | <input type="checkbox"/> 30" x 30" | <input type="checkbox"/> 48" x 48" |
| <input type="checkbox"/> 24" x 60" | <input type="checkbox"/> 30" x 60" | <input type="checkbox"/> 48" x 60" |
| <input type="checkbox"/> 24" x 72" | <input type="checkbox"/> 30" x 120" | <input type="checkbox"/> 48" x 72" |
| <input type="checkbox"/> 24" x 96" | | <input type="checkbox"/> 48" x 96" |
| <input type="checkbox"/> 24" x 120" | | <input type="checkbox"/> 48" x 120" |

(Contact manufacturer for other sizes.)

COLOR/FINISH

- PLAZA White – #5300P
 Cool Metro Gray – #7000P
 Other # _____

**PERFORATION
PATTERN**

- #144
 Non-Perforated

ACOUSTICAL

_____ (NRC)

TRIM

- Extruded Wall Angle
 Extruded Step Trim
 3-3/4" J-Trim

Color/Finish _____

CUT-OUTS

- Square, Size: _____
 Round, Diameter: _____

EXPOSURE

- Interior


To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
CTSpecialtyCeilings.com

HunterDouglas 
Ceiling & Wall Products
exclusively from CertainTeed

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#144



Perforation dia: .040 in.
Open area: 6%

SOUND ABSORPTION (NRC) SUMMARY*

Sound absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Perforation Pattern	% Open Area	Acoustical Infill	NRC
#144	6%	Non-Woven Acoustic	0.80

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test Reports available upon request.

PHYSICAL DATA

Substrate: Composite Aluminum Honeycomb

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50

Weight: Varies 1.0 - 1.5 lbs./sq.ft.

Wind load: N/A

Recycled content: Up to 85%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81