

Deductions and Light Gap Chart

RB Basics Automated Roller Shades (Small System)

AUTOMATED OUTSIDE MOUNT	Tube & Fabric Deduction									
	Intelligent Wireless RF External Battery		Intelligent Wireless Radio Frequency Control Internal Battery Operated					Intelligent Wireless 24VDC Hardwire	120VAC Motors	
*Single & Dual	OTTO 2NMEB	R28	OTTO 1NM	OTTO 2NM	OTTO 3NM	ST30WF	ST40WF	Sonesse 30 RTS	OTTO 6NM	Sonesse 40 (RTS & WT)
1.25" Tube	N / A	N / A	1.125 in	N / A	N / A	N / A	N / A	N / A	N / A	N / A
1.5" Tube	1.125 in	1.25 in	1.125 in	1.125 in	N / A	1.25 in	N / A	1.125 in	N / A	N / A
2.0" Tube	1.125 in	1.25 in	N / A	1.125 in	N / A	1.25 in	1.375 in	1.125 in	1.375 in	1.5 in
2.5" Tube	N / A	N / A	N / A	N / A	1.375 in	N / A	N / A	N / A	N / A	N / A

AUTOMATED OUTSIDE MOUNT	Tube & Fabric Deduction									
	Intelligent Wireless RF External Battery		Intelligent Wireless Radio Frequency Control Internal Battery Operated					Intelligent Wireless 24VDC Hardwire	120VAC Motors	
3" FASCIA	OTTO 2NMEB	R28	OTTO 1NM	OTTO 2NM	OTTO 3NM	ST30WF	ST40WF	Sonesse 30 RTS	OTTO 6NM	Sonesse 40 (RTS & WT)
1.25" Tube	N / A	N / A	1.125 in	N / A	N / A	N / A	N / A	N / A	N / A	N / A
1.5" Tube	N / A	1.25 in	1.125 in	1.125 in	N / A	1.25 in	N / A	1.125 in	N / A	N / A
2.0" Tube	N / A	1.25 in	N / A	1.125 in	N / A	1.25 in	N / A	1.125 in	1.375 in	1.5 in
2.5" Tube	N / A	N / A	N / A	N / A	N / A	N / A	N / A	N / A	N / A	N / A

AUTOMATED OUTSIDE MOUNT	Tube & Fabric Deduction									
	Intelligent Wireless RF External Battery		Intelligent Wireless Radio Frequency Control Internal Battery Operated					Intelligent Wireless 24VDC Hardwire	120VAC Motors	
4" FASCIA	OTTO 2NMEB	R28	OTTO 1NM	OTTO 2NM	OTTO 3NM	ST30WF	ST40WF	Sonesse 30 RTS	OTTO 6NM	Sonesse 40 (RTS & WT)
1.25" Tube	N / A	N / A	1.125 in	N / A	N / A	N / A	N / A	N / A	N / A	N / A
1.5" Tube	1.125 in	1.25 in	1.125 in	1.125 in	N / A	1.25 in	N / A	1.125 in	N / A	N / A
2.0" Tube	1.125 in	1.25 in	N / A	1.125 in	N / A	1.25 in	1.375 in	1.125 in	1.375 in	1.5 in
2.5" Tube	N / A	N / A	N / A	N / A	1.375 in	N / A	N / A	N / A	N / A	N / A

AUTOMATED OUTSIDE MOUNT	Tube & Fabric Deduction									
	Intelligent Wireless RF External Battery		Intelligent Wireless Radio Frequency Control Internal Battery Operated					Intelligent Wireless 24VDC Hardwire	120VAC Motors	
5" FASCIA	OTTO 2NMEB	R28	OTTO 1NM	OTTO 2NM	OTTO 3NM	ST30WF	ST40WF	Sonesse 30 RTS	OTTO 6NM	Sonesse 40 (RTS & WT)
1.25" Tube	N / A	N / A	1.375 in	N / A	N / A	N / A	N / A	N / A	N / A	N / A
1.5" Tube	1.375 in	1.5 in	1.375 in	1.5 in	N / A	1.375 in	N / A	1.375 in	N / A	N / A
2.0" Tube	1.5 in	1.5 in	N / A	1.5 in	N / A	1.5 in	1.625 in	1.375 in	1.625 in	1.75 in
2.5" Tube	N / A	N / A	N / A	N / A	1.75 in	N / A	N / A	N / A	N / A	N / A

Above measurements are Outside Mount.

For Inside Mount, add 0.125" to the deduction above.

For End Caps, No Fascia, add 0.125" to the deduction above.

For End Caps, 3", 4" or 5" Fascia, add 0.25" to the deduction above.