

Installation Instructions

HunterDouglas 
Architectural



RB 500+ Manual **Roller Shades**

with Standard Brackets - Inside Mount

Window Coverings

Hunter Douglas Architectural Window Coverings continues to deliver expertly engineered solutions to manage light and glare control.

This booklet provides installation instructions that can be used as a stand alone piece or may accompany video instructions at bit.ly/2vm9z2p

RB 500+ Manual
Roller Shades
with Standard Brackets - Inside Mount

HunterDouglas 
Architectural

Materials Needed



Power Drill, 5/32" & 1/8" Drill Bits, 5/16" Hex Driver



Steel Tape



Pencil



Flat Blade and Philips Screwdrivers



2" Screws #10



Needle Nose Pliers



Laser Level

Copyright © 2019 Hunter Douglas Architectural

Hunter Douglas Architectural Window Coverings
13915 Danielson Street
Suite 100
Poway, CA 92064
United States

HDarchitectural.com



9

Install the clutch end of the shade onto the tab on the clutch-side bracket. The bottom of the clutch should always point straight down. Finally, push the idle end into the shade and place into the idle end bracket.



10

Secure the shade by turning the locking ring away from the bracket. At this point, the tape band and child safety tag can safely be removed.



11

Now is a good time to check that the shade is level and aligned.



12

When mounting the cord tensioner, first remove the pin from the tensioner. Realign the cord tensioner's screw hole at the bottom and reinsert the pin to hold in place. Slide the tensioner to the bottom of the beaded chain.



13

Now you're ready to attach the cord tensioner to the inside of the window casement. Before installing, pre-drill your holes using the 1/8" drill bit. Once you have found your placement, remove the pin and place a screw through the aligned hole.

Place the bead stop at the desired height on the back chain, using pliers to fasten. Next, lower the shade and check your lower limit. Place the bead stop at the desired height on the front chain.

14



Pull on both sides of the chain loop to ensure the shade is operating in the up and down direction.

15



UnInstallation Process

**1**

Start by unscrewing the cord tensioner.

**2**

Loosen the locking ring by turning it in the direction of the bracket.

**3**

Next, using a flat blade screwdriver, push the idle into the shade while pulling the shade towards you. This will allow you to pull the clutch end out of the clutch bracket.

**4**

Finally, remove the screws and brackets.

Congratulations!

You have now successfully installed and uninstalled an outside mounted RB 500+ Manual Roller Shade with Heavy Duty Brackets.

RB500+ Manual **Roller Shade**

with Standard Duty Brackets - Inside Mount

INSTRUCTIONAL VIDEO

<https://bit.ly/2NPafGB>

HunterDouglas 
Architectural