

SUBMITTAL SHEET

NATURA™ NEO™ GLADIUS™

(Semi-Concealed 15/16" T-Grid)

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE

Class A 3/4" FR PB

PANEL WIDTH

(12" wide up to 72" long,
or 24" x 24")

12"x 24" 24"x 24"
 12"x 36" Other: _____
 12"x 48"
 12"x 60"
 12"x 72"

FINISH

Veneer # _____ FSC

PERFORATION PATTERN

#C201 #C203 #C212 Non-Perforated
 #C202 #C204 #C213

ACOUSTICAL BACKER

Black Non-Woven
 None

ACOUSTICAL RATING

_____ (NRC)

FLOATING PERIMETER TRIM

Extruded Aluminum Edgeline Trim, veneer to match
Height: 4" 6" Other: _____

FACTORY CUT-OUTS

Square; Size: _____ Round; Diameter: _____

EXPOSURE

Interior Only

Shop Drawings required on all Natura™ NEO™ projects.

To Contact Us:


5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
HDarchitectural.com

HunterDouglas 
Architectural

PERFORATIONS


Perforated panels improve acoustical performance as well as create aesthetic effects.

#C201




Perforation diam: .196 in.
Open area: 2.0%

#C202




Perforation diam: .314 in.
Open area: 5.0%

#C203




Perforation diam: .196 in.
Open area: 4.0%

#C204




Perforation diam: .314 in.
Open area: 10.0%

#C212



Perforation diam: .984 in.
Open area: 12.0%

#C213



Perforation diam: .984 in.
Open area: 6.0%

SOUND ABSORPTION (NRC) SUMMARY*

Sound absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Perforation Pattern	% Open Area	Acoustical Infill	NRC
#C203	4%	Non-Woven Acoustic	0.40
#C204	10%	Non-Woven Acoustic	0.60

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: FR Composite Wood

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

– Wood veneer on FR Board: Flame spread: ≤ 25, Smoke ≤ 95

Weight: Varies 3.0 – 4.0 lbs./sq.ft.

Wind load: N/A

Light reflectance: Varies with veneer and finish