

SUBMITTAL SHEET

HEARTFELT™ LINEAR

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE Felt: Non-woven thermo-formable PES fibers

PROFILE 1-9/16" x 2-3/16"

SPACING 1-15/16" o.c. (50 mm) module, 3/8" reveal
 2-3/8" o.c. (60 mm) module, 13/16" reveal
 3-1/8" o.c. (80 mm) module, 1-9/16" reveal

COLOR/FINISH Off-White - #7595F Dark Grey - #7598F
 Light Grey - #7596F Anthracite - #7599F
 Middle Grey - #7597F

ACOUSTICAL RATING _____ (NRC)

EXPOSURE Interior Only

To Contact Us:
5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
HDarchitectural.com

HunterDouglas 
Architectural

SUBMITTAL SHEET HEARTFELT™ LINEAR

SOUND ABSORPTION (NRC) SUMMARY*

Panel Spacing	Openness	Reveal	NRC
1-15/16" (50 mm)	20%	3/8"	0.70
2-3/8" (60 mm)	33%	13/16"	0.60
3-1/8" (80 mm)	50%	1-9/16"	0.50

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Non-woven thermo-formable PES fibers

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E1264

– Flame spread: ≤ 25, Smoke ≤ 300

Weight: Varies

Wind load: N/A

Recycled content: Up to 85%

Light reflectance (LR): Varies with color selected

Given the unique and special nature of our HeartFelt™ ceiling product, steps should be taken (before and during installation, as well as over the lifetime of the ceiling) to avoid or minimize static and the accumulation of dust, lint, dirt or airborne particles on or around the felt. Hunter Douglas does not warrant against or take responsibility for any such static or accumulation.