

# SUBMITTAL SHEET

## DEEP BOX SERIES

Project Name \_\_\_\_\_

Specification Section \_\_\_\_\_

Ceiling Type \_\_\_\_\_

**Return Form To Hunter Douglas**

**E-mail: [ceiling.samples@hunterdouglas.com](mailto:ceiling.samples@hunterdouglas.com)**

**Fax: 770.806.0214**

### SUBSTRATE

Aluminum

### PROFILE

Deep Box 2    Deep Box 4    Deep Box 6    Deep Box 8 (.032" thickness only)

### COLOR/FINISH

Cotton White – #0280  
 Natural – #7163  
 Other # \_\_\_\_\_

### FILLER STRIP

Box Flat Recessed Closure – Matte Black – #1883    Open Reveal  
 Box Flat Recessed Closure – Cotton White – #0280  
\* Filler Strip required for all Exterior applications.

### ACOUSTICAL BACKER

Black Polywrapped Pad  
 None  
\* For use with interior perforated material only.

### ACOUSTICAL RATING

\_\_\_\_\_ (NRC – Achieved via Open Reveals)

### TRIM

Wall Angle    Edgeline (interior only) \_\_\_\_\_  
 Floating J-Trim    End Caps

Color/Finish: # \_\_\_\_\_

### EXPOSURE

Interior  
 Exterior - Design Wind Pressure (required) \_\_\_\_\_ PSF

**Shop Drawings required on all Exterior projects.**

#### To Contact Us:

5015 Oakbrook Parkway, Suite 100  
Norcross, GA 30093  
phone: 800.366.4327  
fax: 770.806.0214  
HDarchitectural.com

**HunterDouglas**   
Architectural

# SUBMITTAL SHEET **DEEP BOX SERIES**

## **SOUND ABSORPTION (NRC) SUMMARY\***

<b>Product</b>	<b>Acoustical Infill</b>	<b>NRC</b>
Deep Box 2, non-perforated, open reveal	1" – 1.5 pcf Polywrapped Fiberglass	0.65
Deep Box 2, non-perforated, open reveal	2" – 1.5 pcf Polywrapped Fiberglass	0.90

\* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting.

## **PHYSICAL DATA**

---

**Substrate:** Aluminum

**Warranty:** 1 year

**Seismic rating:** Zones A,B,C,D,E,F

**Fire rating:** Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55 (for interior applications)

**Weight:** Varies 0.5 – 0.75 lbs./sq.ft.

**Wind load:** Per code (for exterior applications)

**Recycled content:** Up to 92%

**Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:**

- Cotton White: LR = 0.81