

SUBMITTAL SHEET

HIGH PROFILE SERIES™ STRAIGHT BAFFLE

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

SUBSTRATE

Extruded Aluminum

PROFILE

(Width x Height)

Beam

1-1/2" x 4-3/8"

1-1/2" x 6-3/8"

1-1/2" x 8-3/8"

2" x 4"

2" x 6"

2" x 8"

4" x 4"

* Length – minimum 2'-0", maximum 20'-0"

Aero

1-5/8" x 6-3/8"

Sweep

1-3/4" x 6-3/8"

Open Beam

4" x 4"

Taper

1-1/2" x 8"

Crescent

4" x 6-3/8"

Other – contact Hunter Douglas

BEAM SPACING

6"

8"

12"

Other _____

COLOR/FINISH

Beam Finish

Cotton White – #0280

Natural – #7163

Other _____

* Veneer and Wilsonart® finishes (interior only) are profile-specific; contact Hunter Douglas.

Hanger Bracket Finish

Black

White

Painted to match plenum

END CAPS

Yes

No

GRAIN DIRECTION

(For Decorated or Veneer End Caps)

Horizontal

Vertical

SPLICES

Yes

No

EXPOSURE

Interior

Exterior* – Design Wind Pressure (required) _____ PSF

* Exterior applications are project-specific and must be reviewed and approved by Hunter Douglas prior to quote.

Shop Drawings required on all High Profile Exterior projects.

To Contact Us:

5015 Oakbrook Parkway, Suite 100

Norcross, GA 30093

phone: 800.366.4327

fax: 770.806.0214

HDarchitectural.com

HunterDouglas 
Architectural

SUBMITTAL SHEET **HIGH PROFILE SERIES™ STRAIGHT BAFFLE**

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25 , Smoke ≤ 50
- Wood veneer on metal: Flame spread: ≤ 25 , Smoke ≤ 55

Weight: Varies 2.0 - 4.0 lbs./sq.ft.

Wind load: Per Code

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81