SUBMITTAL SHEET

HIGH PROFILE SERIES™ STRAIGHT BAFFLE

	Form To Hunter Douglas ceiling.samples@hunterdouglas.com
Ceiling T	/pe
Specific	tion Section
Project I	ame

SUBSTRATE	Extruded Aluminum					
PROFILE (Width x Height)	☐ Beam — choose size: ☐ 1-1/2" x 4-3/8" ☐ 1-1/2" x 6-3/8" ☐ 1-1/2" x 8-3/8" ☐ 2" x 8" ☐ 4" x 4"			 □ Aero (1-5/8" x 6-3/8") □ Sweep (1-3/4" x 6-3/8") □ Beam – Open (4" x 4") □ Other – contact Hunter Douglas 		
BEAM SPACING	□ 6"	□ 8"	□ 12"	☐ Other		
COLOR/FINISH	Beam Finish ☐ Cotton White - #0280 ☐ Natural - #7163 ☐ Other * Veneer and Wilsonart® finishes (interior only) are profile-specific; contact Hunter Douglas. Hanger Bracket Finish ☐ Black ☐ White ☐ Painted to match plenum					
END CAPS	☐ Yes	□ No				
GRAIN DIRECTION For Decorated or Veneer End Caps)	☐ Horizontal	☐ Vertical				
SPLICES	☐ Yes	□ No				
EXPOSURE	☐ Interior ☐ Exterior* — Design Wind Pressure (required)PSF * Exterior applications are project-specific and must be reviewed and approved by Hunter Douglas prior to quote.					

Shop Drawings required on all High Profile Exterior projects.

To Contact Us: 5015 Oakbrook Parkway, Suite 100 Norcross, GA 30093 phone: 800.366.4327 fax: 770.806.0214 HDarchitectural.com



SUBMITTAL SHEET HIGH PROFILE SERIES™ STRAIGHT BAFFLE

PHYSICAL DATA

Substrate: Aluminum Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
 Wood veneer on metal: Flame spread: ≤ 25, Smoke ≤ 55

Weight: Varies 2.0 - 4.0 lbs./sq.ft.

Wind load: Per Code

Recycled content: Minimum of 50%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Cotton White: LR = 0.81