

SUBMITTAL SHEET

MULTI-BOX CONTINUOUS

Project Name _____

Specification Section _____

Ceiling Type _____

Return Form To Hunter Douglas

E-mail: ceiling.samples@hunterdouglas.com

Fax: 770.806.0214

PATTERN

- | | | |
|----------------------------------|----------------------------------|--------------------------------------|
| <input type="checkbox"/> Alpha | <input type="checkbox"/> Foxtrot | <input type="checkbox"/> Other _____ |
| <input type="checkbox"/> Bravo | <input type="checkbox"/> Golf | (Specify pattern and start point) |
| <input type="checkbox"/> Charlie | <input type="checkbox"/> Hotel | |
| <input type="checkbox"/> Delta | <input type="checkbox"/> India | |
| <input type="checkbox"/> Echo | <input type="checkbox"/> Juliet | |

COLOR/FINISH

- Cotton White – #0280
 Natural – #7163
 Other _____

FILLER STRIP

- Box Flat Recessed Closure – Matte Black – #1883 Open Reveal
 Box Flat Recessed Closure – Cotton White – #0280
* Filler Strip required for all Exterior applications

PERFORATION PATTERN

- | | | | |
|-------|---|------------|---|
| Box 2 | <input type="checkbox"/> Non-Perforated | Deep Box 2 | <input type="checkbox"/> Non-Perforated |
| Box 4 | <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 4 | <input type="checkbox"/> Non-Perforated |
| Box 6 | <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 6 | <input type="checkbox"/> Non-Perforated |
| Box 8 | <input type="checkbox"/> Non-Perforated <input type="checkbox"/> #160 | Deep Box 8 | <input type="checkbox"/> Non-Perforated |

ACOUSTICAL BACKER

- Black Non-Woven
 Black Polywrapped Pad
 None
* For use with interior material only.

ACOUSTICAL RATING

_____ (NRC)

TRIM

- Wall Angle Edgeline (interior only) _____
 J-Trim End Caps

Color/Finish: # _____

EXPOSURE

- Interior
 Exterior - Design Wind Pressure (required) _____ PSF

Shop Drawings required on all Multi-Box projects.

To Contact Us:

5015 Oakbrook Parkway, Suite 100
Norcross, GA 30093
phone: 800.366.4327
fax: 770.806.0214
HDarchitectural.com


HunterDouglas 
Architectural

SUBMITTAL SHEET MULTI-BOX CONTINUOUS

PERFORATIONS

Perforated panels improve acoustical performance as well as create aesthetic effects.

#160



Perforation diam: .060 in.
Open area: 23%
(Box 4, 6 and 8 only)

SOUND ABSORPTION (NRC) SUMMARY*

Sound Absorption can be achieved by the addition of backing ceiling panels with acoustical fabric or pad.

Product	Acoustical Infill	NRC
Linear Multi-Box "Alpha" Pattern, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.75
Linear Multi-Box "Bravo" Pattern, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.65
Box 2, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.75
Box 4, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 4, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85
Box 6, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.65
Box 6, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 6, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.80
Box 8, non-perforated, open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.50
Box 8, Perforated #160 (23% Open Area), open reveal	1.5" - 1.5 pcf Polywrapped Fiberglass	0.90
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	Nonwoven	0.70
Box 8, Perforated #160 (23% Open Area), with Box Flat Closure Strip	1.5" - 1.5 pcf Polywrapped Fiberglass	0.85

* Acoustical tests performed in accordance with ASTM C423 and ASTM E795, in a type E400 mounting. Test reports available upon request.

PHYSICAL DATA

Substrate: Aluminum

Warranty: 1 year

Seismic rating: Zones A,B,C,D,E,F

Fire rating: Class A Fire Rated per ASTM E84

- Painted or anodized metal: Flame spread: ≤ 25, Smoke ≤ 50
- Film on metal: Flame spread: ≤ 25, Smoke ≤ 50
- Wood veneer on metal: Flame spread : ≤ 25, Smoke ≤ 55 (for interior applications)

Weight: Varies 0.5 – 1.0 lbs./sq.ft.

Wind load: Per code (for exterior applications)

Recycled content: Up to 92%

Light reflectance (LR) Coefficient per ASTM E1264 & ASTM E1477:

- Varies with finish
- Cotton White: LR = 0.81