Duette® FR Honeycomb Shades





The durable, energy-efficient design of our Duette® FR Honeycomb Shades makes them an industry standard. Their superior functionality is ideal for healthcare and assisted living centers, government/military buildings and a wide variety of public spaces. Duette® FR Shades provide exceptional light control, stringent flame retardance and significant insulating and acoustical properties.

SUSTAINABLE CONSTRUCTION

Certified for low emissions by the GREENGUARD Environmental Institute and passes strict requirements of GREENGUARD Children and SchoolsSM.

ENERGY EFFICIENT

The honeycomb design enhances R-value and shading coefficient, and provides 99% UV blocking. Air pockets reduce flow of heat through window, keeping heat in during the winter and out during the summer.

INNOVATIVE DURABILITY

Durable headrail comprised of aluminum alloy accommodates shade widths to 174" and shade heights to 174".

FABRIC COVERED HEADRAIL

Standard with LiteRise® and EasyRise[™] systems

LIFETIME GUARANTEE

Operating Systems



Standard Cordlock



EasyRise™

This continuous cord loop and clutch



LiteRise®

A cordless system with a proprietary design allows you to raise and lower shades with the touch of a finger. No lift cords for a clean, uncluttered look and enhanced safety. Available in 3/4" only.



Top-Down/Bottom-Up



Motorization

to maximize shading benefits.



Specialty Shapes

Options include: arches, angles, trapezoids, circles, hexagons, octagons, and skylights.

Shade sizes vary based on fabric selection and hardware system. See Specifications section in the binder, or visit our website for a complete list of product specifications.

FR Fabrics

Fabrics

- Available in two soft, seamless, non-woven polyester fabrics
- Fabrics meet or exceed all requirements of NFPA 701 small scale flammability testing for commercial applications
- Block 99% of UV light rays to prevent fading
- Fabrics are neutral to the exterior, ensuring a consistent appearance from the outside

Opaque

- 3/4" pleat
- Winter R-value = 5.74*
- Solar shading coefficient = 0.25

Semi-Opaque

- ¾" and ¾" pleat sizes
- 34" Winter R-value = 5.16
- 34" Solar shading coefficient = 0.36
- 3/8" Winter R-value = 5.63
- 3/8" Solar shading coefficient = 0.31

Additional Options

Inside mount / outside mount or end mount, spacer blocks, extension brackets, swivel brackets (inside mount only), end mount brackets, hold-down brackets, cut-outs (surcharge), cord length.



^{*} R-value includes the 3.5 R-value added by a standard low-e double glazed window.

HunterDouglasContract

WINDOW COVERINGS

CEILINGS

SOLAR CONTROL









This brochure was printed using:





By using post consumer recycled fiber in lieu of virgin fiber paper stock:

10 trees were preserved for the future.

28 lbs. of water-borne waste were not created.

4,143 gallons of waste water flow were saved.

458 lbs. of solid waste were not generated.

903 lbs. of net greenhouse gases were prevented.

6,907,950 BTUs of energy were not consumed.

Hunter Douglas Contract Window Coverings 12250 Parkway Centre Drive, Poway, CA 92064 Customer Service: 800.727.8953

Fax: 800.205.9819

www.hunterdouglascontract.com/windowcoverings

© 2009 Hunter Douglas Inc.® and ™ is a trademark of Hunter Douglas Inc.

The GREENGUARD INDOOR AIR QUALITY CERTIFIED mark is a registered certification mark used under license through the GREENGUARD Environmental Institute.